# HP PageWide XL Pro 5200 40-in Multifunction Printer with Pro Stacker



Expand into new short-term applications with instant printing



#### Respond faster to customer demands

- Respond to your customers' requests right away with print speeds up to 20 D/A1 pages/minute.1
- Offer a combination of technical prints and shortterm retail posters, and meet the different demands quickly.
- Deliver full projects 2X faster by printing mixed outputs of both CAD drawings and presentation boards !

#### Expand your offering, printing board applications

- Gain the ability to print on boards, cardstock, and paper from A2 to B1, and thickness up to 3/8 in
- Expand into two-sided, short-term retail posters, and send them to print easily through HP SmartStream
- Get intuitive workflows for a fast learning curve with simple application instructions through HP
- Use responsibly sourced FSC®-certified papers, make recyclable prints, enjoy water-based HP pigment inks.4

#### Help increase revenues and cut costs

- Enable rapid return on investment—grow your offering with a single HP-branded solution.
- Accept new orders and, at the same time, reduce manual work—save up to 50% preparation and finishing costs.5
- Save further—up to 10X lower energy consumption<sup>6</sup>, free supply take-back program<sup>7</sup>, HP Eco-Carton cartridge.

#### For more information, please visit http://www.hp.com/go/pagewidexlpro5200

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

<sup>1</sup> The HP PageWide XL Pro 5200 Multifunction Printer delivers 20 CAD output D/A1 prints in 1 minute. Number of pages will vary depending on the print mode and application printed.
2 Based on testing commissioned by HP and performed by Sogeti in September, 2020 comparing the HP PageWide XL Pro 8200 Printer and a comparable competitive printer that represents the majority market share of LED printers worldwide as of 2019 according to IDC.
Test performed by printing 3 B1 posters on B1 foam and 3 copies of a 6-page file combining sizes A0, A1 and plain, coated paper types. Measuring time from clicking "send" button until last page gets out from out of the printer. Using equivalent print quality mode.
3 HP Learn is accessible through HP PrintOS. Requires an HP PrintOS account, Internet connection, and connected internet-capable device. For more information, see http://www.printos.com.

<sup>4</sup> BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C17543, see http://www.fsc.org. Not all FSC®-certified products are available in all regions. Most HP large format paper-based printing materials can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the free, convenient HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecospolutions for details.

Table to the control of the control of the control of the printer switching commissioned by HP and performed by Sogeti in September, 2020 comparing the HP PageWide XL Pro 8200/5200 Printer series and a comparable competitive printer that represents the majority market share of LED printers worldwide as of 2019 according to IDC, by preparing and printing the job. Test performed by sending 3 copies of a 6-page file combining sizes AQ, A1 and plain, coated paper types. Measuring time from clicking "send" button until last page out of the printer. Printed in fast/CAD equivalent print

Genergy consumption based on testing performed internally by HP based on ISO 20690 and performed September, 2020. Comparable printers using LED technology based on LED printers capable of printing 8-13 D/A1 pages per minute and which represent the majority market share of mid-volume LED printers in the US and Europe according to IDC as of October, 2020.

For free take-back of inner ink bag and printheads, visit http://www.hp.com/recycle to see how to participate and for HP Planet Partners program availability, program may not be available in your jurisdiction. Where this program is not available, and for other consumables

not included in the program, consult your local waste authorities on appropriate disposal

### **Technical specifications**

General	
Description	Large-format color MFP
Technology	HP PageWide Technology
Applications	Line drawings; Maps; Orthophotos; Posters; Double-sided posters; Presentation boards; Wrapping paper
Ink types	Pigment-based (C, M, Y, K)
Ink cartridges	4 (C, M, Y, K)
Cartridge size	1L
Printheads	8 (C, M, Y, K)
Average printhead life	32 L
Printhead warranty	12 months from the date of installation, or 16 L, or until the Warranty Ends date printed on the packaging, whichever comes first
Print resolution	1200 x 1200 dpi
Minimum line width	0.0008 in (HP-GL/2 addressable)
Line accuracy	±0.1% <sup>1</sup>
Print speed	
Technical documents (from roll)	Up to 1100 ANSI D pages/hr, 20 ANSI D pages/min Up to 600 ANSI E pages/hr, 11 ANSI E pages/min
Poster full coverage (from roll)	Up to 4300 ft²/hr, 600 ISO B1 pages/hr, 12 ISO B1 pages/min
Poster full coverage (from input tray)	Up to 1100 ft²/hr, 3 ISO B1 pages/min
Maximum print speed	50 ft/min
Warm-up time	No warm up
First page out	18 sec (from roll and USB), 50 sec (from input tray and USB)
Media	
Media rolls	2 rolls default with auto-switching, expandable to 4 rolls
Roll size	11 to 40 in
Maximum roll diameter	Up to 7 in
Roll core diameter	3 in
Sheet/board size	11.7 to 40.2 in (width), 17.7 <sup>2</sup> to 30.1 <sup>3</sup> in (length)
Standard sheets/boards	Arch B <sup>4</sup> , C, D, E, ANSI B <sup>4</sup> , C, D, ISO B2, B1
Grammage	19 to 53 lb (roll); 1000 gsm (sheet/board)
Media thickness	Up to 15.7 mil (roll); 1/24 in – 3/8 in (sheet/board)
Media types	Bond and recycled papers, poster papers, polypropylene, Tyvek papers, matte film
Media input (standard)	Roll, input tray
Media input (optional)	Pro sheet feeder
Media output (standard)	Pro stacker (500-page capacity), basket
Media output (optional)	Top stacker (100-page capacity), online folder
Scanner	Top steers. (1997 page supersy), statute steers
Description	36-in (91-cm) CIS scanner
Speed	Color: up to 6 in/sec
Optical resolution	Grayscale: up to 10 in/sec
Scan width	Up to 36 in
-	
Original thickness  Maximum copy length	0.01 in 374.5 in
Maximum scan length	164 ft (PDF), 39 ft (TIFF), 26 ft (JPEG) <sup>5</sup>
Scan format	JPEG, TIFF, Multi-TIFF, PDF, PDFA, multi-PDF, multi-PDFA
Scan features	Live preview, scan quicksets, smart background removal, black enhancement, automatic de-skew, reduce scan
Scan destination	speed, post-edit settings (contrast, brightness, rotation, cropping and skew)  Printer storage, USB drive, network folder (SMB), My home folder, scan to email, scan to HP SmartStream software
Embedded controller	
Processor	Intel Core i3
Memory	16 GB DDR4
Hard drive	1 x 128 GB SSD, 1 x 500 GB HDD, both self-encrypted with AES-256
Native print languages	HP-GL/2, TIFF, JPEG, Adobe PostScript 3, Adobe PDF 1.7
Remote management	HP Partner Link, HP Embedded Web Server, HP Web Jetadmin, PrintOS
Connectivity	C. Luci (2000 T) (60.20)
Interfaces Printing paths	Gigabit Ethernet (1000Base-T), USB 2.0 host  HP SmartStream software (optional), HP Click printing software (optional), HP PageWide XL print drivers (PDF, HP-
Here to be of the	GL/2, and PCL3), Apple AirPrint
User interface	ATC: 1/00 ATT/(FDI) II: IMAGO ( AUG. W
User interface	15.6-inch (396-mm) TFT (LED blacklight) 16:9-format HD capacitive touchscreen

Dimensions (W x D x H)	
Printer	77 x 80.3 x 55.7 in
Shipping	88.9 x 40.9 x 62.8 in
Weight	
Printer	1367 lb
Shipping	1640 lb
Environmental	
Operating temperature	41 to 104ºF
Operating humidity	20 to 80% RH, depending on media type
Acoustics	
Sound pressure	$\leq$ 60 dB(A) (operating), $\leq$ 36 dB(A) (idle), $\leq$ 20 dB(A) (sleep)
Sound power	≤7.8 B(A) (operating), ≤5.5 B(A) (idle), ≤3.5 B(A) (sleep)
Power	
Consumption	0.29 kW (typical); 0.9 kW (max printing); 100 W (ready); <18 W (sleep)
Requirements	Input voltage (auto ranging) 200-240 V (±10%), 50/60 Hz (±3 Hz), 5 A
Certification	
Safety	IEC 60950-1+A1+A2 and IEC 62368-1 2nd ed. compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 and 62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KC)
Environmental	ENERGY STAR, EPEAT Registered, UL 2801 ECOLOGO, CE marking (including RoHS, WEEE, REACH). In compliance with WW RoHS materials restriction requirements in China, Korea, India, Vietnam, Turkey, Serbia, and Ukraine
Warranty	90 days

## **Ordering information**

Product	
4VW19B	HP PageWide XL Pro 5200 40-in Multifunction Printer with Pro Stacker
Accessories	
5EK00A	HP HD Pro 2 42-in Scanner
5EK01A	HP SD Pro 2 44-in Scanner
8SB02A	HP PageWide XL Drawer
8SB05A	HP PageWide XL Pro Sheet Feeder
8SB09A	HP PageWide XL Folder Upgrade Kit for Long Plots
8SF70A	HP F70 Folder
CZ320B	HP PageWide XL Top Stacker
Original HP larg	e format printing materials

HP Universal Bond Paper, 3-in Core (FSC® certified)<sup>6</sup> (recyclable)<sup>7</sup>
HP Production Matte Poster Paper, 3-in Core (FSC® certified)<sup>6</sup> (recyclable)<sup>7</sup>
HP Production Satie Poster Paper, 3-in Core (FSC® certified)<sup>6</sup> (recyclable)<sup>7</sup>
HP Universal Heavyweight Coated Paper, 3-in Core (FSC® certified)<sup>6</sup> (recyclable)<sup>7</sup>
HP Matte Polypropylene, 3-in Core

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

- <sup>1</sup> ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Polypropylene and HP PageWide XL pigment
- <sup>2</sup> 420 mm (16.5 in) supported only in boards.

- \*\*-4.20 mm (16.5 m) supported only in loards.

  \*\*3 Longer lengths may be supported depending on the accessories installed.

  \*\*4A3 (Arch B and ANSI B) supported only in boards.

  \*\*5 Scanned at 200 dpi. PDF scanning available on PostScript models only.

  \*\*6 BMG trademark license code FSC®-C115319, see http://www.fsc.org, HP trademark license code FSC®-C017543, see http://www.fsc.org, Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please wish thtp://www.HPLFMedia.com.

  \*\*7 Can be recycled through commonly available recycling programs.























